

WP490G 2017 HIGHLIGHTS

- 4.3" color display 480*272
- Caller image
- 2 x Gigabit Port 10/100/1000
- Audio HD wideband
- Max 16 BLF keys (2 pages)
- 802.3az Green Ethernet
- Support of WPEHS
- PBX phonebooks
- Max 30 BLF keys (2 pages) + up to 3 extension modules
- Support of WP490EXT
- PoE IEEE 802.3af
- Quick DND key
- VM notification
- Visual/ audio BLF
- Presence monitoring



TECH SPECIFICATIONS

Phone & PBX

- Presence
- New Voicemail / Missed call / New call notification
- Online access to PBX phonebooks
- Sync of call history and missed call notifications
- PBX ringtones
- Intercom, paging, speed dial, hold, 3-way conference call; redial, mute, call transfer, call pickup, group call pickup, music on hold
- Multi-language support

Audio

- HD audio with wideband codec G.722
- Narrowband codec G.711a, ulaw, G.729
- Full-duplex speaker
- Echo canceller

Security & Networking

- SIP TLS; QoS VLAN; RTP/RTCP

Physical

- 30 BLF (20 physical + 10 software keys)
- 4.3" color display with backlight 480*272
- 1 x RJ9 headset port; 1 x RJ9 handset port; 1 x EXT port
- 802.3az Green Ethernet
- Optional Power Adapter: Input AC 100-240 V; Output DC 5 V / 1 A
- Max power consumption: WP490G: 5.51W; WP490 + 1 ext. module: 10,26W; WP490G + 2 ext. modules: 11.04W
- PoE IEEE 802.3af Class 0
- 2 x RJ45 10/100/1000 Mb Ethernet ports
- 285.5*224*96,2 mm, 1.23 kg
- Operating t°: 32~104 °F, 0~40 °C; Storage t°: 14~122 °F, -10 ~ 50 °C; Humidity: 10 to 90 % Non-condensing