

W-AIR Basic is The Basic phone for massive installations.

FEATURES - W-AIR BASIC

- 1,44" 128x128 display
- PRESENCE
- HD wide band audio
- Integrated phonebooks
- CAT-iq
- Loudspeaker
- 3.5 mm headset jack
- Optional case with belt clip



W-AIR Basic

TECH SPECIFICATIONS - W-AIR BASIC

DECT

Maximum transmission power:

EU: 250mW (24.0dBm)

US: 100mW (20.0dBm)

Frequency bands:

1880 – 1900MHz (EU)

1920 – 1930MHz (US)

Range:

Indoor: 50m

Outdoor: 300m

One antenna

Encryption supported

AUDIO

G722 wideband codec

HD audio speakerphone

HAC compliant (TIA-1083)

DISPLAY

1,44" 128x128 pixels color display TFT

Multilanguage

KEYPAD

21 keys total

2 soft keys

ON- and OFF-hook keys

HEADSET OPTIONS

3.5mm headset jack

Compatible headsets: WHS-MONO, WHS-DUO

3rd party headsets: <https://confluence.wildix.com/x/DASIAQ>

RINGER

Volume control

Silent ringer

Adjustable alert (low battery, low coverage)

Handsfree mode (Loudspeaker)

CALL FEATURES

PBX phonebook

Local phonebook with 50 entries

Call waiting, Call on hold, Conference call, Call Swap

Up to 2 channels/ calls

POWER PERFORMANCE

Talk time: 8h(NB), 7h(WB)

Standby time: 75hours

Charge time: 10 hours

Charging conditions: +5°C to 40°C

SIZE AND WEIGHT

Size: 135 x 41 x 25mm

Weight: 108g

ENVIRONMENTAL

IP20 housing

Operating conditions: 0 to 40°C

Relative Humidity: 20%-80%

RELIABILITY SPECIFICATIONS

Drop height: 1m

Keypad lifetime: 40.000 presses

Keypad abrasion: Standard

APPROVALS

Radio: EN 301 406

EMC: EN 301 489-1, EN 301 489-6

Safety: EN 60950-1; FCC part 15

ACCESSORIES

Optional case with belt clip (code: WAIR-Basic-8PC, a bundle of 8 pieces)

W-AIR datasheets:

